



INVELCO, S.A.

INVESTIGACIONES ELECTRONICAS Y COMUNICACIONES

invelco@invelco.com



www.invelco.com

SELCAL ENCODER MODEL SC-600-A



- Ergonomic design.
- Easy to operate.
- Earth/air selective call all in one unit.
- Highly visible LCD display.
- Code input through frontal keyboard.
- Computer interface through RS-232-C connector.
- Auxiliary relay for PTT and audio switching.
- Optional SELCAL 32.



The SC-600-A SELCAL Encoder conforms to the requirements of ANRIC 714-6 "MARK—3 AIRBORNE SELCAL SYSTEM", Part III, Ground Selective Calling Unit.

The SC-600-A is housed in a self-contained 19" unit, that includes a keyboard and a display.

*Ergonomic design
and
Easy to operate*

SELCAL ENCODER MODEL SC-600-A

TECHNICAL CHARACTERISTICS

GENERAL SPECIFICATIONS

Power supply	220Vac \pm 20%, 50/60 Hz.
Consumption	40W.
Measurements:	
Width	19" (482.5 mm).
Height	1 U (44.0 mm).
Depth	320 mm.
Weight	5 kg.
Ergonomic knobs and buttons.	
Code display of great visibility.	
Grey colour texture paint.	

TECHNICAL SPECIFICATIONS

Number of tones	16 / 32 (optional).
Tones stability	\pm 10%; 0°C to 50°C.
Tones balance	\pm 0.5dB.
Maximum output level	\pm 10dB (adjustable)
Noise and buzzing	Less than -40dB.
Codes input	16 buttons
Codes reading	4 characters display
Cancellation button.	
Send button.	
Transmission and send indication.	